

ONE HOSE SYSTEM

Micro-Jet Tornado

Tornado power

- maximum blasting power
- high area coverage
- for the most stubborn of soiling
- ideal for pipe cleaning and paint removal

Standard equipment:

- basic and functional equipment
- hopper attachment for 20 kg more dry ice filling capacity
- membrane filter
- sub micro filter
- compressed air treatment
- automatic ground roll
- Tornado Plus blast gun with RD 8 nozzle
- blast hose package 7 meter with PVC sleeve



Micro-Jet Tornado

Technical specification:

Net weight:	60 kg (132 lbs), stainless steel housing
Dimensions:	(W x L x H) 365 x 575 x 1340 mm (14 x 23 x 53 inch)
Dry ice filling capacity:	35 kg (77 lbs)
Dry ice consumption:	90 kg/h (199 lbs)
Operating pressure:	max. 16 bar (232 psi)
Blasting pressure:	max. 16 bar (232 psi)
Compressed air consumption:	3 m ³ /min - 12 m ³ /min, depending on the selected nozzle combination
Compressed air requirements:	clean, oil-free, free of foreign bodies and dry (pressure dew point below 10°C)
Compressed air connection:	DIN 3489 claw coupling
Power connection:	not necessary, system works purely pneumatically
Noise:	60 dB (A) - 120 dB (A), depending on nozzle combination and surface of the object being blasted
Article number:	240 000